## Listing of Claims

 (Original) Method of segmenting a three-dimensional structure from a threedimensional data record, containing in particular medical data values, comprising the steps of:

- a) providing a three-dimensional, deformable model whose surface area is formed by a network of meshes, which connect together points of the network on the surface area of the model, the meshes being divided into groups and each group being allocated a structure function.
- arranging the model at the position in the three-dimensional data record in which the structure to be segmented is located,
- determining one candidate point for each mesh with the aid of the structure function of the group to which the mesh concerned belongs,
- d) recalculating the points of the network of the model on the basis of the candidate points found,
- repeating steps c) and d), taking the newly calculated points of the network into account, as long as no termination criterion is met.
- 2. (Original) The method as claimed in Claim 1, step a) comprising the following steps:
- providing a three-dimensional, deformable model whose surface area is formed by a network of meshes, which connect together points of the network on the surface area of the model,
- comparing each mesh with each adjacent, neighbouring mesh with the aid of a similarity criterion.
- gathering together into groups neighbouring meshes which are similar in accordance with the similarity criterion,
  - assigning a structure function to each group.
- 3. (Original) The method as claimed in Claim 1, step a) comprising the following steps:

providing a three-dimensional, deformable model in each case in a plurality
of data sets, all the models having the same number of meshes and the meshes in each
model having the same neighbourhood relationships,

- gathering together the meshes of all the models into groups,
- assigning the meshes with the same neighbourhood relationships to the group in which those meshes are contained most frequently,
- assigning one structure function to each group,
- taking the average of the models of the three-dimensional data sets in order to determine a deformable model.
- 4. (Previously Presented) The method as claimed in Claim 1, wherein the fact that, in step c), from a set of points, that point is selected as the candidate point of a mesh for which the structure function exhibits an extreme, especially a maximum
- 5. (Previously Presented) The method as claimed in Claim 1, wherein the fact that, in step c), a candidate point of a mesh is found in that position on a normal of the surface area enclosed by the mesh at which the structure function exhibits an extremum, especially a maximum.
- 6. (Previously Presented) The method as claimed in Claim 1, wherein the fact that the value of the structure function in a particular position in the threedimensional data record is a measure of the probability that that particular position is located on a surface area of the structure to be segmented.
- 7. (Previously Presented) The method as claimed in Claim 1, wherein the fact that, in step d), the points of the network are recalculated, while minimising a weighted sum of external and internal energy.
- (Original) An image processing device for performing the method of Claim 1
   with
- a memory unit for storing at least one deformable model whose surface area is formed by a network with meshes connecting points of the network on the surface area

of the model, and for storing at least one three-dimensional data record, containing in particular medical data values,

- an image reproduction unit for reproducing a structure to be segmented, or already segmented, and the at least one deformable model.
- a calculator unit for recalculating the points of the network of the at least one model.
- an arrangement unit for arranging the model, at the position in the threedimensional data record at which the structure to be segmented is located,
  - a control unit for controlling the memory unit, the image reproduction unit, the calculator unit and the arrangement unit in accordance with the following steps:
    - a) providing a three-dimensional, deformable model whose surface area is formed by a network of meshes, which connect together points of the network on the surface area of the model, the meshes being divided into groups and each group being allocated a structure function,
    - arranging the model at the position in the three-dimensional data record in which the structure to be segmented is located,
    - determining one candidate point for each mesh with the aid of the structure function of the group to which the mesh concerned belongs,
    - recalculating the points of the network of the model on the basis of the candidate points found,
    - repeating steps c) and d), taking the newly calculated points of the network into account, as long as no termination criterion is met,
- (Currently Amended) A <u>computer-readable medium comprising a computer</u> program for a control unit for controlling a memory unit, an image reproduction unit, a calculator unit and an arrangement unit of an image processing device for carrying out the method of Claim 1 in accordance with the following steps:
- a) providing a three-dimensional, deformable model whose surface area is formed by a network of meshes, which connect together the points of the network on the surface area of the model, the meshes being divided into groups and each group having a structure function.

b) arranging the model at the position in the three-dimensional data record in which the structure to be segmented is located,

- determining one candidate point for each mesh with the aid of the structure function of the group to which the mesh concerned belongs,
- d) recalculating the points of the network of the model on the basis of the candidate points found,
- e) repeating steps c) and d), taking the newly calculated points of the network into account, as long as no termination criterion is met.